



AUTOMA STANDARD SHEET/BLOCK SIZES												
DV ^{*1}	MATERIAL GRADES ^{*2}	AVAILABLE LENGTHS (mm)									WIDTH (mm) ^{*3}	THICKNESS (mm)
15	S	2000	2500	2750	3000	4000	4500	5000	5500	6000	1220	Cut to order, max is 625mm unskimmed
15	Q		2500					5000				
20	P	2000	2500			4000		5000				
24	P	2000	2500			4000		5000				
32	P		2500					5000				
40	P	2000				4000						
Definitions & notes												
DV: Density value expressed in kg/m ³												
Deviations from standard sizing will incur a cutting charge based on complexity of cutting												
<i>*¹ Density tolerance ± 10%</i>												
<i>*² S=Standard grade, up to 25% recycled content</i>												
<i>*² Q=Quality grade, up to 15% recycled content</i>												
<i>*² P=Premium grade, 100% virgin material</i>												
<i>*² S, Q & P grades are produced from type FR (fire retarded) material. Fire retarded EPS foam when exposed to heat shrinks away from the heat source. The probability of ignition of the material is significantly reduced and welding sparks or cigarettes normally will not ignite it.</i>												
<i>*³ Width on full blocks would be ± 1230mm. This would be the unskimmed width.</i>												